HY-RAIL® Model MD1920



The Harsco Rail MD1920 HY-RAIL® guide wheel equipment is used to adapt medium-duty chassis cab trucks, meeting Harsco Rail's recommended vehicle specifications, for railway applications requiring travel on the highway and on the rail. Featuring hydraulic deployment, hydraulic locks, electrical track insulation, and mechanical safety pins, the MD1920 has a rugged, compact design that continuously provides the durability needed on the track.



HY-RAIL® MD1920 Specifications

Features & Benefits

- For medium duty trucks cab chassis
- High road clearance
- Front unit over center rotation in rail position
- Rear unit positions guide wheels close to trucks tires

Truck Weight Classification	Medium duty - up to 19,500 lbs. (8844 kg) GVWR	Harsco Rail M 200 South Jac Ludington, M Tel: +1 231 8 E-Mail: railinfo
Maximum Rail Travel Speed	35 mph (55 km/h)	
Unit Weight	Front unit - 415 lbs. (188 kg)	Protran Techr 1960 Old Cut
	Rear unit - 425 lbs. (193 kg)	Suite 100 Cherry Hill, N
Load Capacities (max)	Front unit - 7,000 lbs. (3,175 kg)	Tel: +1 856 7 E-Mail: info@p
	Rear unit - 6,750 lbs. (3,062 kg)	Harsco Rail P 4 Strathwyn S
Guide Wheel Load (max)	Front wheels - 3,500 lbs. (1,588 kg) each	Brendale Queensland 4
	Rear wheels - 3,375 lbs. (1,531 kg) each	Tel: +61 7 32
Suspension	Rear unit has built-in spring suspension	Harsco Rail L Unit 1, Chew
Wheels	13.25 in. (337 mm) tread diameter	Nottingham N Tel: +44 (0) 1
Wheel Bearings	Conventional wheel / hub bearing arrangement	Email: uksale: Harsco Rail L
Safety Pin Locks	Mechanical pin plus hydraulic PO check locks	Av. Marechal Centro
Raise / Lower Operation	Electrical / hydraulic actuation with push button controllers	Rio de Janeiro Tel: +55 21 2
Track Gauge	56.5 in. (1435 mm)	Harsco Rail E Luetticher Str 40547 Duess
Track Signal Insulation	All (4) guide wheels electrically insulated for track signaling	Tel: +49 (0) 2 E-Mail: info@l
Included Equipment	Mounting brackets, steering wheel lock, de-rail guards, front rail sweeps	Harsco Rail C Room C1201 No.36 BeiSan DongCheng D
Optional Equipment	Hydraulic power pack, emergency hand pump, air brakes (front and rear), rear rail sweeps, non-electrical track insulation	Beijing 10001 Tel: +87 10-6 Harsco Track

Download full specs at www.harscorail.com

Harsco Rail Global Headquarters

3440 Torrington Way Suite 100, Building 3 Charlotte, NC 28277, USA

Main Tel: +1 803 822-9160 Email: railinfo@harsco.com www.harscorail.com



Bulletin #S-01B-0116 Updated in USA, September 2018





© 2016 Harsco Corporation

AREMA R

Harsco Rail, Harsco Corporation Facility Locations:

Harsco Rail Global Headquarters 3440 Toringdon Way Suite 100, Building 3 Charlotte, NC 28277, USA Tel: +1 980 960-2624 E-Mail: railinfo@harsco.com

Harsco Rail Manufacturing Operations 2401 Edmund Road, Box 20 West Columbia, SC 29171-0020, USA Tel: +1 803 822-9160 E-Mail: railinfo@harsco.com

Harsco Rail Engineering Center 306 West 4th Street Fairmont, MN 56031-1837, USA Tel: +1 507 235-7376 E-Mail: railinfo@harsco.com

Harsco Rail Manufacturing Operations 200 South Jackson Road Ludington, MI 49431, USA Tel: +1 231 843-3431 E-Mail: railinfo@harsco.com

Protran Technology 1960 Old Cuthbert Road Suite 100 Cherry Hill, NJ 08034, USA Tel: +1 856 779-7795 E-Mail: info@protrantechnology.com

Harsco Rail Pty Ltd Australia 4 Strathwyn Street, P.O. Box 5287 Brendale Queensland 4500, Australia Tel: +61 7 3205 6500

Harsco Rail Ltd United Kingdom Unit 1, Chewton Street, Eastwood Nottingham NG16 3HB, United Kingdom Tel: +44 (0) 1773 539480 Email: uksales@harsco.com

Harsco Rail Ltda Brazil Av. Marechal Câmara, 160 / 1615, Centro Rio de Janeiro RJ 20020-080, Brazil Tel: +55 21 2510-5164 / -5151

Harsco Rail Europe GmbH Luetticher Str. 130 40547 Duesseldorf, Germany Tel: +49 (0) 211 60116 0 E-Mail: info@harsco-r.de

Harsco Rail China Room C1201 Tower 2, No.36 BeiSanHuan Dong Lu, DongCheng District, Beijing 100013, P.R. China Tel: +87 10-6590-6399

Harsco Track Machines and Services Private Limited India 2nd Floor, Building Alpha, Bengal Intelligent Park Block EP & GP, Sector V, Salt Lake, Kolkata 700091 West Bengal, India Tel: +91 33 2357 5651

The HARSCO RAIL equipment pictured in this brochure is intended to illustrate the general appearance and features of this product. It is equipped as specified by a particular customer and may or may not show items that are optional or recommended by HARSCO RAIL, Harsco Corporation. Specifications, illustrations, and descriptive materials herein were accurate as known at the time this publication was approved for printing. HARSCO RAIL, Harsco Corporation reserves the right to discontinue models or options at any time or change specifications and materials, equipment and design without notice and without incurring obligation. Federal, State or Provincial, and/or local laws and regulations may require additional equipment for the particular use intended for this product. It is the buyer's responsibility to determine the applicability of such laws and regulations to the buyer's intended use for the product and to arrange for the installation of the required equipment. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies and/or mark holders.