

UTILITY TRACK VEHICLE

FOR TRACK AND CATENARY MAINTENANCE



UTILITY TRACK VEHICLE FOR TRACK AND CATENARY MAINTENANCE

Harsco Rail's diesel-electric Utility Track Vehicle, for track and catenary maintenance, is flexibility innovated. Modularized traction system, car body arrangement, and work equipment enable simple configurability, while delivering unparalleled performance.

From zero emissions to travel speeds up to 160 km/h, the Utility Track vehicle can be tailored to each customer's unique needs – whether servicing emission-strict metropolitan areas or quickly reaching distant work sites.



FEATURES

Modularity

The vehicle can be configured to customer requirements - the traction system, car body, and work equipment are adjustable to the application.

Performance

The vehicle can be offered with a travel speed of up to 160 km/h. In the diesel-electric configuration, power ratings of the diesel engines can be adapted to the required performance. Providing a maximum of up to 1.000 kW, while being able to offer a system redundancy within the traction system.

Hybrid Technology

Integration of battery packages with different capacities is possible. The hybrid technology enables the operator to use the vehicle with zero emissions in work-mode. At the same time the battery can be used to enable a Boost-Mode for a short period whenever the extra in power is needed.

Dual-Mode Technology

The Vehicle can be equipped with Dual-Mode technology, which allows the vehicle to travel with pure electric traction via overhead catenary and switch back to traction via diesel-engine when no overhead catenary is available.

An exceptional power rating of over 1.000 kW enables the vehicle to run with low emissions, while reducing maintenance and fuel-consumption cost. Energy recuperation in the overhead catenary is also possible.

Environmental Friendly

Focus on environmental-friendly technologies is part of our company DNA. Fulfilling the newest emission standards for diesel-engines (Stage V) and integrating a trendsetting, natural-refrigerant air conditioning system is a matter of course for us.

Additional options are available to further decrease noise emissions.

Lifecycle Cost

Harsco Rail's focus on state-of-art technologies and control systems ensures operational benefits are passed on to our customers through reduced maintenance cost and lower fuel consumption. The Utility Track Vehicle's smart energy management control system combines different power sources, enabling battery power storage or energy recuperation in the overhead catenary line.



Environmental Friendly



Customized Modularity



Exceptional Performance



Efficient Operating Costs

UTILITY TRACK VEHICLE

FOR TRACK AND CATENARY MAINTENANCE



SPECIFICATIONS

Length	24640 mm
Width	2786 mm
Height	Dependent on roof installations
Track Gauge	1435 mm
Max. Axle Load	20 t
Superelevation	200 mm
Min. Curve Radius	90 m
Max. Gradient	40 – 61,4 ‰
Train Protection System	National Train Control System / ETCS 3.6.0
Max. Travel Speed	120 km/h, options: 140 and 160 km/h
Working Speed	0 - 10 km/h
Diesel-Engine	up to over 1000 kW possible
Emission Standard	Stage V
Optional Battery Capacity	Different capacities possible
Optional Dual-Mode Technology	Diesel-Electric and Electric-Electric

Learn more at harscorail.com



Updated in USA, August 2019

Harsco Rail, Harsco Corporation
Facility Locations:

Harsco Rail Global Headquarters
3440 Toringdon Way
Suite 100, Building 3
Charlotte, NC 28277, USA
+1 980 960-2624
railinfo@harsco.com

Harsco Rail Manufacturing Operations
2401 Edmund Road, Box 20
West Columbia, SC 29171-0020, USA
+1 803 822-9160
railinfo@harsco.com

Harsco Rail Engineering Center
306 West 4th Street
Fairmont, MN 56031-1837, USA
+1 507 235-7376
railinfo@harsco.com

Harsco Rail Manufacturing Operations
200 South Jackson Road
Ludington, MI 49431, USA
+1 231 843-3431
railinfo@harsco.com

Protran Technology
1960 Old Cuthbert Road, Suite 100
Cherry Hill, NJ 08034, USA
+1 856 779-7795
info@protrantechnology.com

Harsco Rail Pty Ltd Australia
4 Strathwyn Street, P.O. Box 5287
Brendale, Queensland 4500, Australia
+61 7 3205 6500

Harsco Rail Ltd United Kingdom
Unit 1, Chevton Street, Eastwood
Nottingham NG16 3HB, United Kingdom
+44 (0) 1773 539480
uksales@harsco.com

Harsco Rail Ltda Brazil
Av. Marechal Câmara, 160 / 1615, Centro
Rio de Janeiro RJ 20020-080, Brazil
+55 21 2510-5164 / -5151

Harsco Rail Europe GmbH
Luetticher Str. 130
40547 Duesseldorf, Germany
+49 (0) 211 60116 0
info.emea@harsco.com

Harsco Rail China
Room C1201 Tower 2,
No.36 BeiSanHuan Dong Lu,
DongCheng District,
Beijing 100013, P.R. China
+87 10-6590-6399

Harsco Track Machines and Services
Private Limited India
2nd Floor, Building Alpha,
Bengal Intelligent Park Block EP & GP,
Sector V, Salt Lake, Kolkata
700091 West Bengal, India
+91 33 2357 5651

The HARSCO RAIL equipment pictured in this brochure is intended to illustrate the general appearance and features of this product. It is equipped as specified by a particular customer and may or may not show items that are optional or recommended by HARSCO RAIL, Harsco Corporation. Specifications, illustrations, and descriptive materials herein were accurate as known at the time this publication was approved for printing. HARSCO RAIL, Harsco Corporation reserves the right to discontinue models or options at any time or change specifications and materials, equipment and design without notice and without incurring obligation. Federal, State or Provincial, and/or local laws and regulations may require additional equipment for the particular use intended for this product. It is the buyer's responsibility to determine the applicability of such laws and regulations to the buyer's intended use for the product and to arrange for the installation of the required equipment. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies and/or mark holders.