

UTILITY/SPOT TAMPER

MODEL 3000



UTILITY/SPOT TAMPER

FEATURES

- Rail Lifting (Manual) – Lifting & Lining
- Air Conditioner
- Fire Extinguisher
- West Coast Mirrors
- Work, Travel & Brake Lights
- Turn-table
- Amber Strobe
- Electric Controls
- 8.5' Travel Width

AVAILABLE OPTIONS

- Light Reference (Manual) – Lifting & Lining
- Spare Parts
- Low Air Pressure Alarm
- Hydraulic Tank Filling System
- Jackfeet Extension Option

For switches, crossovers or production tamping and lining, the 3000 Utility and Spot Tamper delivers exceptional tamping quality and accuracy. Compact yet powerful, the 3000 is equipped with the same high performance, heavy-duty workheads as our premium 6700 tamper. The benefit to you: outstanding reliability and productivity.

Just as important, the 3000's economical electrically controlled hydraulic design greatly simplifies maintenance procedures and makes trouble-shooting routine. And that helps keep downtime to a minimum.

The 3000 is a superb all-around performer. Its rugged design makes it economical to purchase, operate and maintain.

SPECIFICATIONS

Travel Speed & Gradability	9% Grade @ 5 mph (8 kph), 3.5% Grade @ 14 mph (22 kph), 1% Grade @ 35 mph (55 kph)
Maximum Speed	35 mph (55 kph)
Chassis	Structural tubing framework
Wheels	20 inches (508 mm) diameter
Axles	Pillow block mounted, 4 inch (102 mm) diameter alloy steel with outboard wheels
Length	21 feet (6.4 m)
Width (traveling)	8 feet - 6 inches (2.59 m)
Width (working with jacks)	11 feet - 8 inches (3.5 m)
Height Over Rail	11 feet - 6 inches (3.5 m)
Weight	27,500 pounds (12,245 kg)
Wheel Base	8 feet (2.4 m)
Engine	Cummins Diesel OSB6.7 - 174 hp @ 2500 rpm
Controls	Manual hydraulic
Propulsion System	Hydraulic drive, 3-speed transmission to front axle
Brakes	Hydro-dynamic, 4-wheel fail-safe air brakes
Fuel Tank Capacity	105 U.S. gallons (400 liters)
Hydraulic Tank Capacity	105 U.S. gallons (400 liters)
Tamping System	Two independent carriages with four independent vibratory squeeze tamping units, individually positioned for switch tamping, eight vibrators provide 4500 vpm
Derail Protection	Derail bars located near axles

Learn more at harscorail.com



Harsco Rail, Harsco Corporation
Facility Locations:

Harsco Rail Global Headquarters
3440 Toringdon Way
Suite 100, Building 3
Charlotte, NC 28277, USA
+1 980 960-2624
railinfo@harsco.com

Harsco Rail Manufacturing Operations
2401 Edmund Road, Box 20
West Columbia, SC 29171-0020, USA
+1 803 822-9160
railinfo@harsco.com

Harsco Rail Engineering Center
306 West 4th Street
Fairmont, MN 56031-1837, USA
+1 507 235-7376
railinfo@harsco.com

Harsco Rail Manufacturing Operations
200 South Jackson Road
Ludington, MI 49431, USA
+1 231 843-3431
railinfo@harsco.com

Protran Technology
1960 Old Cuthbert Road, Suite 100
Cherry Hill, NJ 08034, USA
+1 856 779-7795
info@protrantechology.com

Harsco Rail Pty Ltd Australia
4 Strathwyn Street, P.O. Box 5287
Brendale, Queensland 4500, Australia
+61 7 3205 6500

Harsco Rail Ltd United Kingdom
Unit 1, Chewton Street, Eastwood
Nottingham NG16 3HB, United Kingdom
+44 (0) 1773 539480
uksales@harsco.com

Harsco Rail Ltda Brazil
Av. Marechal Câmara, 160 / 1615, Centro
Rio de Janeiro RJ 20020-080, Brazil
+55 21 2510-5164 / -5151

Harsco Rail Europe GmbH
Luetticher Str. 130
40547 Duesseldorf, Germany
+49 (0) 211 60116 0
info.emea@harsco.com

Harsco Rail China
Room C1201 Tower 2,
No.36 BeiSanHuan Dong Lu,
DongCheng District,
Beijing 100013, P.R. China
+87 10-6590-6399

Harsco Track Machines and Services
Private Limited India
2nd Floor, Building Alpha,
Bengal Intelligent Park Block EP & GP,
Sector V, Salt Lake, Kolkata
700091 West Bengal, India
+91 33 2357 5651

The HARSCO RAIL equipment pictured in this brochure is intended to illustrate the general appearance and features of this product. It is equipped as specified by a particular customer and may or may not show items that are optional or recommended by HARSCO RAIL, Harsco Corporation. Specifications, illustrations, and descriptive materials herein were accurate as known at the time this publication was approved for printing. HARSCO RAIL, Harsco Corporation reserves the right to discontinue models or options at any time or change specifications and materials, equipment and design without notice and without incurring obligation. Federal, State or Provincial, and/or local laws and regulations may require additional equipment for the particular use intended for this product. It is the buyer's responsibility to determine the applicability of such laws and regulations to the buyer's intended use for the product and to arrange for the installation of the required equipment. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies and/or mark holders.