

NEW TRACK CONSTRUCTION



NEW TRACK CONSTRUCTION

Special Features

Harsco Rail's New Track Construction (NTC) machine installs new track on a previously prepared roadbed in a continuous operation. The NTC lays 1.5 km of track per day, improving productivity, safety, efficiency, and quality. The NTC works with concrete, pre-plated wood, or steel ties and provides efficient and effective means to laying new track.

Features & Benefits


- Works with concrete, pre-plated wood, or steel ties
- Rails capable of being laid: Up to 136 lbs
- Approximately 3 times faster than stick building track
- Working Speed: 10 ties per minute
- Controls the flow of material without overhead cranes
- Move ties to the point of attack
- More precise tie spacing and tie squares



Clipping is carried out by a Nipper-Clipper mechanism on the New Track Construction Machine.



Rail Guide rollers suspended from the Laying Beam. Rails are guided into place on ties by an operator positioned below the beam.





Truss Frame

The NTC unit is supported at one end by a specially modified flatcar running on the newly laid track and at the other end, by a non-powered crawler running on the roadbed. The truss frame contains a conveyor system for carrying the crossties down to the tie laying mechanism which places the crossties on the roadbed at a precise and predetermined spacing.

Tie Pads

Prior to being positioned on the roadbed, cushioning pads are placed on the ties to cushion the effect of steel rails on concrete ties. The entire consist is pulled by a crawler-type auxiliary power unit.



Gantries

A self-propelled gantry, requiring one operator, keeps the ties supplied to the conveyor systems. The tie handling cars are equipped with auxiliary rails which form a continuous running rail for the gantry. Pivoting extensions between the cars allow the gantry to operate on curves. After being deposited by the gantry, the ties move via the conveyor system to the tie drop area.

Rail Laying/Threading

After the rail has previously been distributed along the roadbed, it is threaded through guides located at the rear of the tow unit. It is then guided inward to a gauging station. Final placing of the rail on the new ties is controlled by an operator who guides the rail onto the tie seat. The operator is also responsible for the proper alignment of the track.

Contract Services

Harsco Rail's New Track Construction Contract Services have installed over 4,000,000 ties (equal to 1,515 miles or 2,400 km). NTC Contract Services provide customers with a high quality service by crews that know the machine's maintenance and operation best.

NEW TRACK CONSTRUCTION

Specifications

Length	Working: 45 m (148 ft.) inclusive of flatcar and front end loader Traveling: 36.5 m (120 ft.) transported on 3 flat cars
Width	On Bogie: 3.24 m (10 ft., 8 in.)
Height	4.72 m (15 ft., 6 in.)
Weight	250 tons - without locomotive
Truss Unit Only	10,886 kg (24,000 lbs.)
Ready to travel on flatcars	101,151 kg (223,000 lbs.)
Recommended tow tractor	Cat 953 track-type front end loader
Working Speed	10 ties per minute
Travel Speed	Towed by locomotive for track travel-up to 80 km/h (50 mph)
Rails capable of being laid	Up to 136 lbs.
Min Curve Radius	Working: 144 m (478 ft.) 12 degrees Traveling: 97.5 m (320 ft.) 18 degrees

Gantries

Length	8.6 m (28.16 ft.)
Width	3.215 m (124 ft.)
Height	6.6 m (15 ft.) above rail
Capacity	Up to 22 ties
Fuel Capacity	379 liters (100 gal.)

Download full specs at www.harscorail.com

Watch video at www.youtube.com/user/harscorail

Harsco Rail Global Headquarters

3440 Torrington Way
Suite 100, Building 3
Charlotte, NC 28277, USA

Main Tel: +1 803 822-9160
Email: railinfo@harsco.com
www.harscorail.com



Bulletin #S-01B-0116

Updated in USA, September 2018

Harsco Rail, Harsco Corporation Facility Locations:

Harsco Rail Global Headquarters
3440 Torrington Way
Suite 100, Building 3
Charlotte, NC 28277, USA
Tel: +1 980 960-2624
E-Mail: railinfo@harsco.com

Harsco Rail Manufacturing Operations
2401 Edmund Road, Box 20
West Columbia, SC 29171-0020, USA
Tel: +1 803 822-9160
E-Mail: railinfo@harsco.com

Harsco Rail Engineering Center
306 West 4th Street
Fairmont, MN 56031-1837, USA
Tel: +1 507 235-7376
E-Mail: railinfo@harsco.com

Harsco Rail Manufacturing Operations
200 South Jackson Road
Ludington, MI 49431, USA
Tel: +1 231 843-3431
E-Mail: railinfo@harsco.com

Protran Technology
1960 Old Cuthbert Road
Suite 100
Cherry Hill, NJ 08034, USA
Tel: +1 856 779-7795
E-Mail: info@protrantech.com

Harsco Rail Pty Ltd Australia
4 Strathwyn Street, P.O. Box 5287
Brendale
Queensland 4500, Australia
Tel: +61 7 3205 6500

Harsco Rail Ltd United Kingdom
Unit 1, Chewton Street, Eastwood
Nottingham NG16 3HB, United Kingdom
Tel: +44 (0) 1773 539480
Email: uksales@harsco.com

Harsco Rail Ltda Brazil
Av. Marechal Câmara, 160 / 1615,
Centro
Rio de Janeiro RJ 20020-080, Brazil
Tel: +55 21 2510-5164 / -5151

Harsco Rail Europe GmbH
Luetticher Str. 130
40547 Duesseldorf, Germany
Tel: +49 (0) 211 60116 0
E-Mail: info@harsco-r.de

Harsco Rail China
Room C1201 Tower 2,
No.36 BeiSanHuan Dong Lu,
DongCheng District,
Beijing 100013, P.R. China
Tel: +87 10-6590-6399

Harsco Track Machines and Services
Private Limited India
2nd Floor, Building Alpha,
Bengal Intelligent Park Block EP & GP,
Sector V, Salt Lake, Kolkata
700091 West Bengal, India
Tel: +91 33 2357 5651

The HARSCO RAIL equipment pictured in this brochure is intended to illustrate the general appearance and features of this product. It is equipped as specified by a particular customer and may or may not show items that are optional or recommended by HARSCO RAIL, Harsco Corporation. Specifications, illustrations, and descriptive materials herein were accurate as known at the time this publication was approved for printing. HARSCO RAIL, Harsco Corporation reserves the right to discontinue models or options at any time or change specifications and materials, equipment and design without notice and without incurring obligation. Federal, State or Provincial, and/or local laws and regulations may require additional equipment for the particular use intended for this product. It is the buyer's responsibility to determine the applicability of such laws and regulations to the buyer's intended use for the product and to arrange for the installation of the required equipment. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies and/or mark holders.