

TRACK STABILIZER

Model TS-30



Harsco Rail's Track Stabilizer, Model TS-30, stabilizes the track by inserting controlled and accurate force directly into the track structure. The operator has the ability to set the desired down-feed pressure for each rail and the machine maintains that constant pressure until the operator changes it. The TS-30 Stabilizer reduces slow orders after tie change-out or undercutting operations.

TRACK STABILIZER

Specifications

Features & Benefits

- Maintains established crosslevel
- Jupiter II Control System
- Comfortable Control Cab
- Color touch screen LCD monitor

Length	13.03 m (560 in.)
Width	2,794 mm (104 in.)
Height	3.8 m (150 in.)
Weight	45,359 kg (100,000 lbs.)
Wheelbase	8.1 m (330 in.)
Frame	High strength boxed beam welded steel construction. Computer designed and analyzed for stress and deflection. Derail protection skids
Wheels/Axles/ Suspension	762 mm (30 in.) diameter multi-wear forged steel wheels mounted on heavy-duty solid railroad type axles
Drive Train	The final drive is essentially the same for both axles and consists of a hydraulic motor direct coupled to a 2-speed power shift transmission
Brakes	Air operated, tread type brakes featuring Cobra® high friction, composition shoes acting on each wheel. Spring applied, air released secondary brake operation provides automatic brake actuation in case of air pressure loss
Engine	Cummins QSB 8.3 liter, 6 cylinder liquid cooled, turbocharged air cooled Diesel, 240 HP (179 kw) @ 2,200 RPM
Operator's Cab	Large, fully enclosed and climatized, mounted on air bags, accessible from either side of the machine via a rear platform and rear entry door
Electrical System	24 VDC with a 175 amp alternator
Jupiter II Control System	Distributed I/O system
Hydraulic System	Variable displacement piston pumps fixed displacement gear pumps, 24 VDC solenoid operated valves
Air System	Engine driven compressor provides pressurized air for positive brake applications and other air operated functions delivering up to 25 scfm depending on speed and turbo boost. 100 psi (690 kpa) operating pressure
Hydraulic Tank Capacity	795 liters (210 gal.)
Fuel Tank Capacity	758 liters (200 gal.)

Download full specs at www.harscorail.com
Watch video at www.youtube.com/user/harscorail

Harsco Rail

2401 Edmund Rd., Box 20
Cayce-West Columbia, SC 29171-0020

Tel: (803) 822-9160
Fax: (803) 822-8107
Email: railinfo@harscorail.com
www.harscorail.com

Bulletin #TS30-01S-0513
Printed in USA, May, 2013

HARSCO
RAIL



Harsco Rail, Harsco Corporation Facility Locations:

2401 Edmund Road
Box 20
Cayce-West Columbia, SC
29171-0020
Tel: (803) 822-9160
Fax: (803) 822-8107

415 North Main St.
Fairmont, MN 56031-1837
Tel: (507) 235-3361
Fax: (507) 235-7370

200 S. Jackson Rd.
Ludington, MI 49431
Tel: (231) 843-3431
Fax: (231) 843-4830

900 Kings Highway North
Suite 208
Cherry Hill, NJ 08034
Tel: (856) 779-7795
Fax: (856) 779-7431

4 Strathwyn St.
P.O. Box 5287 Brendale
Queensland 4500, Australia
Tel: 61 7 3205 6500
Fax: 61 7 3205 7369

Unit 1, Chewton Street, Eastwood
Nottingham NG16 3HB
United Kingdom
Tel: 01773 539480
Fax: 01773 539481

Av. Marechal Camara
160 Grupo 1901
Control CEP: 20020-080
Rio de Janeiro-RG
Tel: (21) 2510-5151
Fax: (21) 2224-3484

Harsco Rail Europe GmbH
Rehhecke 80
40885 Ratingen
Germany
Tel: +49 2102 937200
Fax: +49 2102 37651

Harsco APAC Rail Machinery Trading
(Beijing) Co. Ltd.
Room 805, State Guest Mansion
No. 11 Fuwai Ave.
100037 Beijing, China
Tel: +8610-6800-3286
Fax: +8610-6800-3288

The HARSCO RAIL equipment pictured in this brochure is intended to illustrate the general appearance and features of this product. It is equipped as specified by a particular customer and may or may not show items that are optional or recommended by HARSCO RAIL, Harsco Corporation. Specifications, illustrations, and descriptive materials herein were accurate as known at the time this publication was approved for printing. HARSCO RAIL, Harsco Corporation reserves the right to discontinue models or options at any time or change specifications and materials, equipment and design without notice and without incurring obligation. Federal, State or Provincial, and/or local laws and regulations may require additional equipment for the particular use intended for this product. It is the buyer's responsibility to determine the applicability of such laws and regulations to the buyer's intended use for the product and to arrange for the installation of the required equipment. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies and/or mark holders.