

TRACK STABILIZER

MODEL TS-30



TRACK STABILIZER

MODEL TS-30

FEATURES

- Maintains established cross-level
- Comfortable Control Cab
- Jupiter II Control System
- Color touch screen LCD monitor

Harsco Rail's Track Stabilizer, Model TS-30, stabilizes the track by inserting controlled and accurate force directly into the track structure. The operator has the ability to set the desired down-feed pressure for each rail and the machine maintains that constant pressure until the operator changes it. The TS-30 Stabilizer reduces slow orders after tie change-out or undercutting operations.

SPECIFICATIONS

Length	14.2 m (560 in.)
Width	2,77 mm (109 in.)
Height	3.8 m (150 in.)
Weight	Approximately 100,000 lbs. depending on final machine configuration
Wheelbase	8.5 m (335 in.)
Frame	High strength boxed beam welded steel construction. Computer designed and analyzed for stress and deflection. Derail protection skids
Wheels/Axles/ Suspension	28 in. (711 mm) diameter single-wear solid steel wheels mounted on heavy duty solid railroad type axles
Drive Train	Each axle is fitted with a two speed gearbox directly driven by a variable displacement drive motor providing full time four-wheel drive with automatic speed control. The variable displacement motors provide high torque for starting on grades and seamless transition through travel speeds up to 30 mph (48 kph)
Work Speed	0-3 mph
Brakes	Air operated, tread type brakes featuring Cobraâ, high friction, composition shoes acting on each wheel. Spring applied, air released secondary brake operation provides automatic brake actuation in case of air pressure loss
Engine	Cummins QSB tier 4 6.7 liter, 6 cylinder liquid cooled, turbocharged and charge air cooled diesel, 300BHP (224kW) @ 2200 RPM
Operator's Cab	Large, fully enclosed and climatized, mounted on air bags, accessible from either side of the machine via a rear platform and rear entry door
Electrical System	24 VDC with a 175 amp alternator
Jupiter II Control System	Distributed I/O system
Hydraulic System	Variable displacement piston pumps fixed displacement gear pumps, 24 VDC solenoid operated valves
Air System	The engine mounted air compressor can produce up to 28 SCFM depending on speed and turbo boost pressure. The nominal operating pressure is 100 psi
Hydraulic Tank Capacity	795 liters (210 gal.)
Fuel Tank Capacity	758 liters (200 gal.)

Learn more at harscorail.com

Harsco Rail, Harsco Corporation
Facility Locations:

Harsco Rail Global Headquarters
3440 Toringdon Way
Suite 100, Building 3
Charlotte, NC 28277, USA
+1 980 960-2624
railinfo@harsco.com

Harsco Rail Manufacturing Operations
2401 Edmund Road, Box 20
West Columbia, SC 29171-0020, USA
+1 803 822-9160
railinfo@harsco.com

Harsco Rail Engineering Center
306 West 4th Street
Fairmont, MN 56031-1837, USA
+1 507 235-7376
railinfo@harsco.com

Harsco Rail Manufacturing Operations
200 South Jackson Road
Ludington, MI 49431, USA
+1 231 843-3431
railinfo@harsco.com

Protran Technology
1960 Old Cuthbert Road, Suite 100
Cherry Hill, NJ 08034, USA
+1 856 779-7795
info@protrantechology.com

Harsco Rail Pty Ltd Australia
4 Strathwyn Street, P.O. Box 5287
Brendale, Queensland 4500, Australia
+61 7 3205 6500

Harsco Rail Ltd United Kingdom
Unit 1, Chewton Street, Eastwood
Nottingham NG16 3HB, United Kingdom
+44 (0) 1773 539480
uksales@harsco.com

Harsco Rail Ltda Brazil
Av. Marechal Câmara, 160 / 1615, Centro
Rio de Janeiro RJ 20020-080, Brazil
+55 21 2510-5164 / -5151

Harsco Rail Europe GmbH
Luetticher Str. 130
40547 Duesseldorf, Germany
+49 (0) 211 60116 0
info.emea@harsco.com

Harsco Rail China
Room C1201 Tower 2,
No.36 BeiSanHuan Dong Lu,
DongCheng District,
Beijing 100013, P.R. China
+87 10-6590-6399

Harsco Track Machines and Services
Private Limited India
2nd Floor, Building Alpha,
Bengal Intelligent Park Block EP & GP,
Sector V, Salt Lake, Kolkata
700091 West Bengal, India
+91 33 2357 5651

The HARSCO RAIL equipment pictured in this brochure is intended to illustrate the general appearance and features of this product. It is equipped as specified by a particular customer and may or may not show items that are optional or recommended by HARSCO RAIL, Harsco Corporation. Specifications, illustrations, and descriptive materials herein were accurate as known at the time this publication was approved for printing. HARSCO RAIL, Harsco Corporation reserves the right to discontinue models or options at any time or change specifications and materials, equipment and design without notice and without incurring obligation. Federal, State or Provincial, and/or local laws and regulations may require additional equipment for the particular use intended for this product. It is the buyer's responsibility to determine the applicability of such laws and regulations to the buyer's intended use for the product and to arrange for the installation of the required equipment. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies and/or mark holders.