

SWITCH TAMPING MACHINE

STM



SWITCH TAMPING MACHINE

The Switch Tamping Machine (STM) is a small, truck transportable, tamping machine with Harsco Rail's positive displacement tamping units. The STM provides versatility, simplicity, and quality tamping built on a lower cost platform. This machine can perform spot tamping as well as tandem tamping in production operations. The traversing workheads permit switch tamping as well.

SPECIFICATIONS

Length	6.7 m (21.9 ft.)
Width	3.2 m (10.5 ft.)
Height	3.3 m (11 ft.)
Wheelbase	3.4 m (8.6 ft.)
Track Gauge	1.4 m (4.7 ft.)
Main Frame	Welded steel construction
Wheels and Axles	762 mm (20 in.) cast steel (AAR Profile) wheels on solid alloy steel axles
Suspension	Fixed front axle, rear pivot axle with pillow block bearings mounting to frame
Brakes	Air-operated tread-type shoe brakes with a single composition shoe on each wheel; spring-applied, air-released, parking/emergency brake for automatic brake actuation in case of air pressure loss
Drive Train	Three-speed transmission with hydraulically driven traction motor and chain drive to front axle
Engine	Cummins QSB6.7 liquid cooled diesel
Hydraulic System	Two double pumps operating at 137.9 bar (2,000 psi)
Air System	7.1 L/sec (15 CFM) engine compressor, 689.5 kpa (100 psi) operating pressure
Electrical System	24-VDC system
Cab	Fully enclosed cab is accessible from either side of machine via a side platform equipped with ladder-type steps; provides operator with excellent visibility while working and traveling
Tamping Units	Four hydraulically driven vibrators power 16 abrasion-resistant tools at 50Hz; traversing workheads tamp entire switch area
Optional:	
Leveling System	Harsco Rail Delta System
Lining Systems	Manual curve linear capable of lining both tangent and curved track during tamping and surfacing operations; it consists of an infrared projector and receiver at a fixed distance from the line rail, and a shadowboard at a variable distance from the line rail
Jacking System	Shoulder jacks are located on an overhead jack frame which allows lateral movement of the workheads in tamping a switch

Learn more at hascorail.com



Harsco Rail, Harsco Corporation
Facility Locations:

Harsco Rail Global Headquarters
3440 Toringdon Way
Suite 100, Building 3
Charlotte, NC 28277, USA
+1 980 960-2624
railinfo@harsco.com

Harsco Rail Manufacturing Operations
2401 Edmund Road, Box 20
West Columbia, SC 29171-0020, USA
+1 803 822-9160
railinfo@harsco.com

Harsco Rail Engineering Center
306 West 4th Street
Fairmont, MN 56031-1837, USA
+1 507 235-7376
railinfo@harsco.com

Harsco Rail Manufacturing Operations
200 South Jackson Road
Ludington, MI 49431, USA
+1 231 843-3431
railinfo@harsco.com

Protran Technology
1960 Old Cuthbert Road, Suite 100
Cherry Hill, NJ 08034, USA
+1 856 779-7795
info@protrantechology.com

Harsco Rail Pty Ltd Australia
4 Strathwyn Street, P.O. Box 5287
Brendale, Queensland 4500, Australia
+61 7 3205 6500

Harsco Rail Ltd United Kingdom
Unit 1, Chewton Street, Eastwood
Nottingham NG16 3HB, United Kingdom
+44 (0) 1773 539480
uksales@harsco.com

Harsco Rail Ltda Brazil
Av. Marechal Câmara, 160 / 1615, Centro
Rio de Janeiro RJ 20020-080, Brazil
+55 21 2510-5164 / -5151

Harsco Rail Europe GmbH
Luetticher Str. 130
40547 Duesseldorf, Germany
+49 (0) 211 60116 0
info.emea@harsco.com

Harsco Rail China
Room C1201 Tower 2,
No.36 BeiSanHuan Dong Lu,
DongCheng District,
Beijing 100013, P.R. China
+87 10-6590-6399

Harsco Track Machines and Services
Private Limited India
2nd Floor, Building Alpha,
Bengal Intelligent Park Block EP & GP,
Sector V, Salt Lake, Kolkata
700091 West Bengal, India
+91 33 2357 5651

The HARSCO RAIL equipment pictured in this brochure is intended to illustrate the general appearance and features of this product. It is equipped as specified by a particular customer and may or may not show items that are optional or recommended by HARSCO RAIL, Harsco Corporation. Specifications, illustrations, and descriptive materials herein were accurate as known at the time this publication was approved for printing. HARSCO RAIL, Harsco Corporation reserves the right to discontinue models or options at any time or change specifications and materials, equipment and design without notice and without incurring obligation. Federal, State or Provincial, and/or local laws and regulations may require additional equipment for the particular use intended for this product. It is the buyer's responsibility to determine the applicability of such laws and regulations to the buyer's intended use for the product and to arrange for the installation of the required equipment. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies and/or mark holders.